

ARMY RESEARCH LABORATORY



Hardened Subminiature Telemetry and Sensor Systems (HSTSS) Subsystems Flight Test Results

Eugene M. Ferguson
Lawrence W. Burke, Jr.
Michael S. L. Hollis
Craig R. Myers
Eric S. Irwin
Charles E. Mitchell

ARL-TN-59

February 1996

19960617 132

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

DRDO QUALITY CERTIFICATE 2

NOTICES


Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1996		3. REPORT TYPE AND DATES COVERED Final, Jun 94 - Mar 95
4. TITLE AND SUBTITLE Hardened Subminiature Telemetry and Sensor Systems (HSTSS) Subsystems Flight Test Results				5. FUNDING NUMBERS PR: 1L162618AH80
6. AUTHOR(S) Eugene M. Ferguson, Lawrence W. Burke, Jr., Michael S. L. Hollis, Craig R. Myers, Eric S. Irwin, and Charles E. Mitchell				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: AMSRL-WT-WB Aberdeen Proving Ground, MD 21005-5066				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TN-59
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)				10. SPONSORING/MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) Under the Hardened Subminiature Telemetry and Sensor Systems (HSTSS) Program, two 120-mm M831 projectiles were modified to test the survivability of a multichip module (MCM) and a solid-polymer electrolyte-battery technology. Tests were conducted at the U.S. Army Research Laboratory's (ARL) Transonic Range facility on 6 December 1994 and 8 December 1994. The projectiles experienced launch accelerations of 21,000 g's and 14,000 g's, respectively. Modifications included replacing the M831 spike-nose assembly with a custom-built assembly, which housed an MCM, two solid-polymer batteries arranged with different orientations, and a three-channel FM/FM telemetry system. Malfunctions with the telemetry link on the first firing yielded inconclusive results about the MCM survival of the gun launch; however, this problem did not completely annihilate the evidence which suggested that the solid-polymer batteries survived. Results from the second firing showed that both the MCM and the solid-polymer batteries survived the gun launch.				
14. SUBJECT TERMS telemetry, polymer battery, multichip module (MCM), acceleration, instrumentation				15. NUMBER OF PAGES 27
				16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

The authors would like to express their appreciation to Mr. David J. Hepner, Ms. Elisa A. Jara, and Mr. Louis M. Gobern of the Weapons Technology Directorate (WTD), U.S. Army Research Laboratory (ARL), for their assistance with data reduction. The authors are also indebted to the Transonic Range facility personnel for their technical assistance with the test firing.

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

	<u>Page</u>
ACKNOWLEDGMENTS	iii
LIST OF FIGURES	vii
1. INTRODUCTION	1
2. BACKGROUND	1
3. PRELIMINARY TESTING	2
4. FLIGHT TESTS	4
5. RESULTS	4
6. SUMMARY	16
7. REFERENCES	19
DISTRIBUTION LIST	21

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

<u>Figure</u>	<u>Page</u>
1. MCM mounted to signal conditioning and mixing board	2
2. Encapsulated MCM on shock table	3
3. Typical acceleration profile from shock table	3
4. Layout of components in test vehicle	5
5. Assembled test vehicle	6
6. Telemetry receiving station setup	7
7. AGC signal generated by HST03	9
8. MCM output from HST03	9
9. Horizontal battery output from HST03	10
10. Vertical battery output from HST03	10
11a. Receiver video signal from HST03	11
11b. Receiver video signal from HST03	11
11c. Receiver video signal from HST03	12
12. Waterfall plot of receiver video from HST03	12
13. Output of MCM and batteries from HST03	13
14. AGC signal generated by HST04	14
15. MCM output from HST04	14
16. Horizontal battery output from HST04	15
17. Vertical battery output from HST04	15
18. Yawsonde pulse train from MCM on HST04	17
19. Spin history of HST04	17
20. Yaw history of HST04	18

INTENTIONALLY LEFT BLANK.

1. INTRODUCTION

The Weapons Technology Directorate (WTD) of the U.S. Army Research Laboratory (ARL) at Aberdeen Proving Ground (APG) and the U.S. Army Test and Evaluation Command (TECOM) at Yuma Proving Ground (YPG) are currently conducting a program entitled "Hardened Subminiature Telemetry and Sensor Systems" (HSTSS). This program has been part of the Test Technology Development and Demonstration (TTD&D) Project sponsored by the Director of Test Facilities and Resources, Office of the Secretary of Defense (OSD). HSTSS has been established to develop and demonstrate a new generation of rugged subminiature instrumentation measurement technologies. These new sensor and telemetry components are being designed to withstand shock levels in excess of 100,000 g's and spin rates over 300 rps. The overall goal of this program is to make these devices readily available and affordable to the Army and DOD, in general, for testing smart weapon systems.

2. BACKGROUND

Munition testing is typically performed using external optical and radar-tracking equipment. Although these data are valuable, they do not provide the tester with internal health information, such as the condition of guidance and control systems. Data such as spin, pitch, and yaw rates and pitch and yaw angle for the entire flight are also not realized by only making external measurements. All of these parameters are important when testing and developing smart weapon systems. These measurements combined with external measurement data would provide a complete data package.

The HSTSS program has been chartered to develop and qualify telemetry subsystems and components which will be low cost, small in volume, and able to survive harsh launch environments. This program is developing telemetry transmitters, antennas, conformal power supplies, programmable high-density multichip modules (MCM), physical sensors, and programmable data acquisition chip sets. This modular/component design approach will allow the designer to configure a measurement system to fit practically any form factor. This report discusses the flight test results of a high-g MCM package and of a solid-polymer battery. Both of these technologies have been under evaluation for the HSTSS program.

3. PRELIMINARY TESTING

Both the battery technology and MCM technology had been pretested prior to these flight tests. The solid-polymer batteries have survived shock table tests, spin tests, and air gun tests throughout their development. These batteries have been shown to survive shock levels in excess of 80,000 g's. More detailed data can be found in Burke, Faust, and Mitchell (1994) and Burke, Faulstich, and Newnham (1995).

The MCM package has also been tested using both a shock table and air gun and has routinely survived accelerations in excess of 20,000 g's. More detailed information on these tests can be found in Alper (1993) and Burke et al. (1994).

The signal conditioning and mixing board of the telemetry system was also pretested using the ARL shock table facility. This four-layer printed wiring board consisted mainly of through-hole and surface-mounted electronic components and three Inter-Range Instrumentation Group (IRIG) standard subcarrier oscillators (SCOs). This board also provided connection to the MCM package. The board is shown in Figure 1 with the MCM attached. A spare board with duplicate components, minus the MCM package, was shocked multiple times to levels exceeding 29,000 g's without experiencing any failures. Figure 2 shows the test fixture mounted to the shock table. A typical acceleration profile generated from this shock table is shown in Figure 3.




Figure 1. MCM mounted to signal conditioning and mixing board.




Figure 2. Encapsulated MCM on shock table.




Figure 3. Typical acceleration profile from shock table.

4. FLIGHT TESTS

In order to gun qualify the MCM package and the solid-polymer electrolyte battery, a test vehicle was designed to hold these items and attach them to an existing projectile. The test vehicle chosen was a modified 120-mm, M831, TP-T tank round. The major modification was to replace the screw in spike-nose with a nose section that could hold the MCM package, two polymer batteries, and a three-channel FM/FM telemetry system to monitor component performance. Two of these test vehicles were assembled. Figures 4 and 5 show the layout of the electronics and an assembled unit. Two polymer batteries were used so that the performance at both vertical and horizontal orientations (with respect to the projectile spin axis) could be studied.

The MCM package contained a yawsonde sun-sensor amplifier/mixer circuit and a delay circuit implemented with analog-to-digital and digital-to-analog converters. When functioning properly, the MCM package produces a bidirectional pulse train typical of ARL yawsonde systems (Ferguson, Hepner, and Clay 1993). The polymer-electrolyte batteries were charged to a nominal 3-V level. Once turned on, the batteries were subjected to a 1-K Ω load. Each of the test items was assigned to one of the three channels of the L-band, FM/FM telemetry system, which allowed for continuous monitoring through a radio link. The MCM used the 70-kHz SCO channel, the horizontal battery used the 93-kHz SCO channel, and the vertical battery used the 124-kHz SCO channel.

A ground station for receiving the telemetered data was set up as shown in Figure 6. The ground station consisted of two circularly polarized L-band antennas, two L-band preamplifiers providing a gain of 35 dB, two 100-ft lengths of 1.2 noise figure RF cable, two receivers, and a 14-track analog tape recorder.

5. RESULTS

The vehicles were launched from a smoothbore, 120-mm, M256 cannon at the ARL Transonic Range Facility. The gun was positioned to an azimuth of 202° from true north and a quadrant elevation (QE) of 30°. The first test vehicle, designated HST03, was launched on 6 December 1994 using a charge weight of 4.47 kg to provide an estimated peak acceleration of 21,000 g's.




Figure 4. Layout of components in test vehicle.




Figure 5. Assembled test vehicle.

TELEMETRY RECEIVING STATION




Figure 6. Telemetry receiving station setup.

When acquiring the telemetered data from the test vehicle, the automatic gain control (AGC) signal of one receiver was also monitored. This AGC signal is proportional to the strength of the received signal, and if calibrated, it can be used to measure received signal strength. The AGC signal generated by HST03 is shown in Figure 7 (please note that time = 0 corresponds to projectile muzzle exit in this and all plots in this report). This plot shows that the telemetered signal was being received at about a -60 dBm strength 15 ms prior to muzzle exit. The signal is then greatly attenuated at about 5 ms prior to muzzle exit. This attenuation is typical and is probably due to the formation of ionized gases between the transmitting and receiving antennas in the telemetry link. At muzzle exit, a pulse is generated on the AGC signal. The mechanism which causes this pulse is not yet understood, but it does seem to be an artifact of smoothbore projectile launches that use L-band telemetry systems. After the pulse at muzzle exit, the AGC signal usually rises to its maximum and slowly decreases at a rate inversely proportional to the square of the projectile distance from the receiving antenna; but for HST03, the received signal remained very low until about 18 ms after muzzle exit and only remained strong for about 1.5 ms. This situation is unusual and seems to point to a failure in the telemetry link.

Figures 8, 9, and 10 show the in-bore voltage levels for the three test items. The MCM was at a 2.77-V level, the vertical battery was at 2.4 V, and the horizontal battery was at 1.6 V before the telemetry link was interrupted. The data loss 5 ms prior to muzzle exit is expected based on the examination of the AGC signal.

Fortunately, the 1.5 ms of strong signal was sufficient to conduct at least some analysis. The analog tape was played back at $1/16^{\text{th}}$ speed to examine the receiver video signal at this portion of the flight. Figures 11a, 11b, and 11c show the video signal at the region in question scaled to real time. This data appeared to be periodic and valid for 1.6 ms starting at 18.6 ms after muzzle exit. The periodic portion of the video was then played back at $1/160^{\text{th}}$ speed into a spectrum analyzer. A waterfall plot of the frequency-shifted video signal is shown in Figure 12. The three dominating frequencies in the plot (406 Hz, 574 Hz, and 775 Hz) are $1/160^{\text{th}}$ of realistic values for the three SCOs used for the three channels in the telemetry system. These frequencies were read, scaled to their real-time values, and applied to prelaunch channel calibrations.

Figure 13 shows the results of this processing. The MCM output was 0.1 V, the vertical battery output was 2.5 V, and the horizontal battery output was just under 2.0 V. The output voltage from the MCM was too low and indicates a failure with this component. The MCM failure may have been induced




Figure 7. AGC signal generated by HST03.




Figure 8. MCM output from HST03.




Figure 9. Horizontal battery output from HST03.




Figure 10. Vertical battery output from HST03.




Figure 11a. Receiver video signal from HST03.




Figure 11b. Receiver video signal from HST03.




Figure 11c. Receiver video signal from HST03.




Figure 12. Waterfall plot of receiver video from HST03.




Figure 13. Output of MCM and batteries from HST03.

by the problems with the telemetry system. It can be clearly seen, however, that both vertical and horizontal batteries survived the launch. The horizontal battery even gained about 400 mV, which is a documented characteristic of polymer-electrolyte batteries when they are shocked in this orientation (Burke, Faust, and Mitchell 1994).

The second test vehicle, HST04, was launched on 8 December 1994, under all of the same firing conditions as HST03 except the charge weight. HST04 had 3.57 kg of propellant which accelerated it to a peak of about 14,000 g's. The charge on this round was reduced to increase its probability of survival in light of the problems experienced with HST03.

A portion of the AGC signal for HST04 is shown in Figure 14. The telemetered signal was received at about a -50 dBm strength until about 11 ms prior to muzzle exit. The signal was then greatly attenuated until muzzle exit when the characteristic pulse was generated. Soon after the muzzle exit pulse, the signal strength quickly rose and began to decrease inverse proportionally with projectile distance downrange. AGC signals with this profile are indicative of a properly functioning telemetry link.




Figure 14. AGC signal generated by HST04.




Figure 15. MCM output from HST04.




Figure 16. Horizontal battery output from HST04.




Figure 17. Vertical battery output from HST04.

In-bore and free-flight voltage levels of the three test items are shown in Figures 15, 16, and 17. The MCM's output voltage prior to muzzle exit was at an acceptable level of about 2.3 V. During free flight, bidirectional yawsonde pulses were generated by the MCM (see Figure 18). These pulses and the correct bias voltage indicate that all of the circuitry within the MCM package was functioning properly. The vertical and horizontal batteries seemed to have survived as well. They both had an in-bore voltage of about 2.5 V and a free-flight voltage of essentially 2.5 V. The noise between 10 ms and 40 ms was due to combination of the break in the telemetry link and settling times for the discriminators used to reduce this data. The yawsonde pulse data produced by the MCM were processed to yield the spin rate (solar roll rate) and yaw angle (sigma-n) histories of the test projectile. These data are plotted in Figures 19 and 20.

6. SUMMARY

Test data from HST03 (21,000 g's) showed that the polymer batteries performed well during the interior ballistic regime of launch. (It should be noted that the maximum G-loading is achieved while the projectile is within the bore of the gun.) Very limited telemetry data were available for the free-flight regime; however, there was data that indicated that the polymer batteries survived the launch.

Test data from the MCM on HST03 also indicated that there may have been a failure in either the MCM or its particular telemetry channel. It is not known to the authors what caused the break in the telemetry link; however, the following describe the most probable failure modes based on the observed data:

- a break in the transmitting antenna feed,
- a severely shifting transmitter center frequency, or
- an overly discharged power supply.

Delays during the firing sequence of this round lends credence to the overly discharged power supply scenario.

Test data from HST04 (14,000 g's) showed that both the solid-polymer electrolyte batteries and the MCM performed well throughout the entire flight.




Figure 18. Yawsonde pulse train from MCM on HST04.




Figure 19. Spin history of HST04.




Figure 20. Yaw history of HST04.

Further evaluation and development of both polymer batteries and programmable MCMs, as well as other technologies, will continue under the HSTSS program. This program is currently scheduled for Army funding through FY01 and is also scheduled for Central Test Evaluation Investment Program (CTEIP), OSD funding starting in FY98.

7. REFERENCES

- Alper, D. D. "Programmable Multichip Modules for the Hardened Subminiature Telemetry and Sensor System Program." December 1993.
- Burke, L. W., J. N. Faust, and C. E. Mitchell. "High-G and Spin Testing of Dowty Polymer Battery." ARL-TN-37, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, July 1994.
- Burke, L. W., E. M. Ferguson, D. Alper, J. Banker, and R. Miller. "Programmable MCMs for Low Volume, High-G Applications." Government Microcircuit Applications Conference, San Diego, CA, November 1994.
- Burke, L. W., R. J. Faulstich, and C. E. Newnham. "The Development and Testing of a Polymer Electrolyte Battery for High-G Telemetry Applications." International Power Sources Symposium Proceedings, Brighton, England, April 1995.
- Ferguson, E. M., D. J. Hepner, and W. H. Clay. "Multisensor Pinhole Yawsonde." ARL-TR-213, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, September 1993.

INTENTIONALLY LEFT BLANK.

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	DEFENSE TECHNICAL INFO CTR ATTN DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

3	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TL 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

1	DIRECTOR US ARMY RESEARCH LAB ATTN AMSRL OP SD TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
---	---

ABERDEEN PROVING GROUND

5	DIR USARL ATTN AMSRL OP AP L (305)
---	---------------------------------------

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
1	HQDA ATTN SARD TT DR F MILTON WASHINGTON DC 20310-0103
1	HQDA ATTN SARD TT MR J APPEL WASHINGTON DC 20310-0103
1	NAVAL AIR WARFARE CTR WEAPONS DIVISION ATTN D SCOFIELD CODE P392 TELEMETRY DIV POINT MUGU CA 93042-5000
1	NAVAL AIR WARFARE CTR WEAPONS DIVISION ATTN S GATTIS CODE C3923 TT&I SYS CHINA LAKE CA 93555-6001
1	DIRECTOR REDSTONE TECHL TEST CTR ATTN STERT TE F TD R EPPS REDSTONE ARSENAL AL 35898-8052
2	COMMANDER USA YUMA PROV GR MATL TEST DIR ATTN A HOOPER R FAULSTICH YUMA PROVING GROUND AZ 85365-9110
1	ARNOLD ENG DEV CTR AIR FORCE PM ATTN AEDC DOT P ZEMAN ARNOLD AFB TN 37389-5000
4	DYNAMIC SCIENCE INC ATTN J FAUST C MITCHELL C MYERS E IRWIN PO BOX N ABERDEEN MD 21001

<u>NO. OF COPIES</u>	<u>ORGANIZATION</u>
2	AEDC OPS 620 AVE C MS 6300 J SHAVER G WALKER AEDC TN 37389
1	PRESIDENT AEROSPACE ENERGY SYS INC ATTN W BOYD 3675 S CRAIG CIRCLE SALT LAKE CITY UT 84109
1	ALLD SIGNAL AEROSPACE CO ATTN WAYNE BREM 200 GIBRALTAR RD SUITE 122 HORSHAM PA 19044-2398
2	PICO SYSTEMS INC ATTN J BANKER PO BOX 134001 ANN ARBOR MI 48113-400147
4	STRICOM 12350 RESEARCH PKWY ATTN AMFTI EL O SCHNEIDER AMCPM ITTS I H LASTRA V KREPACKI AMSTI SI J SIRMANS ORLANDO FL 32826-3276
1	THE MITRE CORPORATION ATTN G HAUZE 7525 COLSHIRE DR MCLEAN VA 22102-3481
1	ULTRALIFE BATTERIES ATTN W BREM 1350 RTE 88 S PO BOX 622 NEWARK NY 14513

NO. OF
COPIES ORGANIZATION

ABERDEEN PROVING GROUND

14 DIR, USARL
ATTN: AMSRL-WT-W, C. MURPHY
AMSRL-WT-WB,
L. BURKE, JR. (3 CP)
W. D'AMICO
E. FERGUSON
D. HEPNER
D. VAZQUEZ
M. HOLLIS
F. BRANDON
B. DAVIS
D. MCGEE
T. HARKINS
G. BROWN

NO. OF
COPIES ORGANIZATION

2 ULTRALIFE BATTERIES (UK) LTD
 ATTN DR COLIN NEWNHAM
 18 NUFFIELD WAY ABINGDON
 OXFORDSHIRE OX141TG ENGLAND

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number ARL-TN-59 Date of Report February 1996
2. Date Report Received _____
3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD
ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)

DEPARTMENT OF THE ARMY


OFFICIAL BUSINESS

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO 0001,APG,MD

POSTAGE WILL BE PAID BY ADDRESSEE

DIRECTOR
U.S. ARMY RESEARCH LABORATORY
ATTN: AMSRL-WT-WB
ABERDEEN PROVING GROUND, MD 21005-5066



NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

